



WE DO UNDERLAYMENTS ROOF

10

St. Peters, MO: 636-970-1976
 Pevely, MO: 636-475-3800
 Belleville, IL: 618-233-3278
 Strafford, MO: 417-879-7000
 Hollister, MO: 417-690-4733

| | ROLL SIZE | | | THICKNESS MILS | SELF ADHERING | SURFACE | MEMBRANE | | MAXIMUM EXPOSURE | RELEASE | METAL ROOF |
|--|---|--|-------|---|---------------|----------------------|-------------------------|--|----------------------|---------|------------|
| | 1 SQ. | 1.5 SQ. | 2 SQ. | | | | SBS | ASPHALT | | | |
| ICE & WATER PROTECTION | all require a temperature of 40° F and rising. All require a primer if applying over concrete, stone or exterior gypsum | | | | | | | | | | |
| MOISTURE GUARD PLUS - TAMKO High temperature up to 250° | Yes | Yes | Yes | 55 mils | Yes | Granule Non-skid | Yes | No | 90 days | Split | No |
| TW UNDERLAYMENT - TAMKO High temperature up to 245° | NO | No | Yes | 40 mils | Yes | Textured Skid Resist | No | Yes Rubberized | 90 days | Single | Yes |
| TW Metal & TILE - TAMKO High temperature up to 245° | No | No | Yes | 75 mils | Yes | Textured Skid Resist | No | Yes | 90 days | Split | Yes |
| WEATHER WATCH® - GAF | No | Yes | Yes | 40 mils | Yes | Mineral Skid Resist | | | 60 days | Split | No |
| STORMSHIELD - IKO | No | No | Yes | 55 mils | Yes | Sanded | Yes | No | Do not leave Exposed | Split | Yes |
| WEATHERLOCK - Owens Corning | Yes | No | Yes | 53 mils | Yes | Granule Slippery | Yes | No | Unknown | Split | No |
| LIONGUARD - CARLISLE | Yes | No | Yes | 55 mils | Yes | Granule Slip Resist | No | Yes Rubberized | 30 days | Split | No |
| SYNTHETIC UNDERLAYMENTS | Roll Size | COMPOSITION | | THICKNESS | Color | TEAR RESIST | SKID RESIST | ADVANTAGES | | | |
| TAMKO SYNTHETIC | 10 sq | TPO, fiberglass scrim, polyethylene back | | 8 mils | Cool Gray | Yes | Yes | Lay lines, Marked cap nail locations as well as High Wind nail cap locations | | | |
| SHARKSKIN COMP Use with fiberglass based & modified bitumen based shingles and metal roofs | 10 sq | Polyolefin coated fabric | | Not stated | White/Grey | Yes | Yes | Lay lines, install with standard EG roofing nails & hammer tacker staples | | | |
| SHARKSKIN ULTRA 320° melt point - use with shingles, metal, real & synthetic slate & clay & concrete tile roofs | 10 sq | 100% polypropylene product - 12 Month UV exposure rating | | Not stated | White/Grey | Yes | Yes | Installs with 3/8" roofing nails. No plastic caps required. 12 month UV exposure rating. Weighs only 45 lbs./roll. | | | |
| ATLAS SUMMIT SYNTHETIC Good to 300° F. Use with shingles, metal, clay tile, slate, concrete tiles, wood shingles | 10 sq | Woven polypropylene fabric. 6 month UV resistant | | Not stated | Green | Yes | Good walking traction | Weighs only 30 lbs/roll Lay lines. Must use 1" Plastic cap nails | | | |
| GAF DECK-ARMOUR Use with shingles, metal, tile and slate. | 10 sq | Spun bound polypropylene for easier cutting. 6 month UV | | Not stated | White/Grey | Yes | Exceptional Walkability | Weighs 37 lbs/roll. Must use 1" plastic cap nails or plastic cap staples. Perm rating of 16. | | | |
| FELTS | | | | | | | | | | | |
| 15 # Felt (4 sq/roll) | 30 # Felt (2 sq/roll) | | | Shingle-Mate - GAF (4 sq/roll) - glass reinforced felt - steep slope | | | | | | | |
| 15 U.L. Felt Tamko (4 sq/roll) | 30 U.L. Felt (2 sq/roll) | | | Gorilla Guard - Atlas (4 sq roll) - glass reinforced felt - steep slope | | | | | | | |